Cryolys® Evolution





Cooling unit for sensitive sample preparation

- Efficient cooling: before, during and after processing
- No need for compressed air and power supply
- Accurate temperature monitored by Precellys® Evolution Touch software
- Minimal bench space





CRYOLYS® EVOLUTION

KEEP YOUR THERMO-SENSITIVE MOLECULES «IN SHAPE»!

Monitored low temperature ensures the integrity of specific molecules such as proteins and RNA, giving downstream analysis better efficiency and sensitivity.

Cryolys® Evolution is the only patented integrated cooling unit preventing the increase of temperature during lysing. Based on dry ice sublimation, it enhances the efficiency of molecular extraction, resulting in premium quality analysis, maintaining the desired

temperature between 0 and 10°C before and during homogenization.

Thanks to its ingenious design, the Cryolys® Evolution is now a real extension of the Precellys® Evolution Touch homogenizer. Positioned on the unit's lid, the system is powered and managed directly by the Precellys® Evolution Touch software, offering a complete control of the temperature during samples grinding with a limited bench space.

Principle

1. The Cryolys® Evolution is connected directly to the top of the dedicated Precellys® lid.



tubes without

Cryolys

2. Ambiant air is aspirated in and cooled in contact with dry ice.



3. Cold air is then sprayed into the Precellys lid to maintain the thermosensitive molecules in their original state.




Detachable cooling module: 1,3kg


Bertin Technologies - February 2023 - Copyrights: Bertin / IStock / T. Léaud

Tubes temperature profile

7500rpm, 3x30s, 30s breaks



With Cryolys sitive samples are preserved!



Precellys homogenizers range











Technical specifications

Size 335x335x100mm Full unit: 2.6kg Weight

Capacity 1,5kg of dry ice

Dry ice consumption 1,5kg for 30min (run time)

Norms CF

Noise < 60dB

Unit plugged to a Precellys® Evolution Touch / Minimal heigh Requirement over bench: 70cm / Minimal depth of the bench: 70cm

Catalog number P000671-CLYS2-A

Discover our comprehensive range of solutions



AIR SAMPLING







TECHNOLOGY ON-DEMAND



Bertin Technologies S.A.S • Parc d'Activités du Pas du Lac • 10 bis, avenue Ampère, 78180 Montigny Le Bretonneux, France www.bertin-technologies.com